## Honeywell

### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron Performax™ LT

MSDS Number : 000000013866

Product Use Description : Refrigerant

Manufacturer or supplier's

details

Honeywell International Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Form : Liquefied gas

Color : clear and colourless

Odor : ether-like

#### Classification of the substance or mixture

Classification of the : Gases under pressure, Liquefied gas

substance or mixture Simple Asphyxiant

#### GHS Label elements, including precautionary statements

## Honeywell

## Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Symbol(s) :

 $\Diamond$ 

Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements : **Storage:** 

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise

classified

: May cause frostbite.

May cause cardiac arrhythmia. May cause eye and skin irritation.

#### Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
1,1,1,2-Tetrafluoroethane	811-97-2	40.00 %
Difluoromethane	75-10-5	30.00 %
Pentafluoroethane	354-33-6	30.00 %

#### **SECTION 4. FIRST AID MEASURES**

## **Honeywell**

#### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Inhalation : Move to fresh air. If breathing is irregular or stopped,

administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : The product is not flammable.

**ASHRAE 34** 

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Contents under pressure.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray. Vapours are heavier than air and can cause suffocation by

Page 3 / 16

## Honeywell

### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

reducing oxygen available for breathing.

In case of fire hazardous decomposition products may be

produced such as: Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

for firefighters

Special protective equipment : Wear self-contained breathing apparatus and protective suit.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Wear personal protective equipment.

> Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

The product evapourates readily.

Methods for cleaning up : Ventilate the area.

#### **SECTION 7. HANDLING AND STORAGE**

#### Handling

Handling : Wear personal protective equipment.

Do not breathe vapour.

Page 4 / 16

## Honeywell

### Genetron Performax™ LT

#### 000000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Avoid contact with skin, eyes and clothing.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Keep away from heat.

Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

#### Storage

Requirements for storage areas and containers

Pressurized container: protect from sunlight and do not expose

to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Page 5 / 16

### Genetron Performax™ LT

### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Do not get in eyes, on skin, or on clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

**Exposure Guidelines** 

Exposure Guidelines					
Components	CAS-No.	Value	Control	Upda	Basis
			parameters	te	
1,1,1,2- Tetrafluoroethane	811-97-2	TWA: time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
		-			
1,1,1,2-	811-97-2	TWA:	4,240 mg/m3	2007	WEEL:US. AIHA
Tetrafluoroethane		time	(1,000 ppm)		Workplace
		weighted			Environmental
		average			Exposure Level
					(WEEL) Guides

# **Honeywell**

## Genetron Performax™ LT

## 000000013866

Version 1.5	Revision Date 06/04/2014	Print Date 05/28/2015

Pentafluoroethan e	354-33-6	TWA : time weighted average	4,900 mg/m3 (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
Pentafluoroethan e	354-33-6	TWA : time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
Difluoromethane	75-10-5	TWA : time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides
Difluoromethane	75-10-5	TWA : time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : Liquefied gas

Color : clear and colourless

Odor : ether-like

pH : Note: neutral

Boiling point/boiling range : -45.5 °C at 1,013 hPa

Flash point : Note: not applicable

Page 7 / 16

## Honeywell

#### Genetron Performax™ LT

#### 00000013866

Revision Date 06/04/2014 Print Date 05/28/2015 Version 1.5

Lower explosion limit : Note: None

Upper explosion limit : Note: None

Vapor pressure : 10,218 hPa

> at 21.1 °C(70.0 °F) 24,621 hPa at 54.4 °C(129.9 °F)

Vapor density : Note: not determined

Density : Note: not determined

Partition coefficient: n-

: log Pow: 1.06

Note: 1,1,1,2-tetrafluoroethane (HFC-134a) octanol/water

log Pow: 1.48

Note: Ethane, pentafluoro- (HFC-125)

: Note: no data available Ignition temperature

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

Page 8 / 16

## Honeywell

### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to

avoid

: Potassium Calcium

Powdered metals

Finely divided aluminium

Magnesium

Zinc

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as:

Gaseous hydrogen fluoride (HF).

Carbonyl halides Carbon monoxide Carbon dioxide (CO2)

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Acute inhalation toxicity

1,1,1,2-Tetrafluoroethane : LC50: > 500000 ppm

Exposure time: 4 h

Species: rat

Difluoromethane : LC50: > 520000 ppm

Exposure time: 4 h

Species: rat

Pentafluoroethane : > 769000 ppm

Exposure time: 4 h

Species: rat

Sensitisation

1,1,1,2-Tetrafluoroethane : Cardiac sensitization

Species: dogs

Note: No-observed-effect level

50 000 ppm

Lowest observable effect level

75 000 ppm

Page 9 / 16

## Honeywell

### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Difluoromethane : Cardiac sensitization

Species: dogs

Note: No-observed-effect level

>350 000 ppm

Pentafluoroethane : Cardiac sensitization

Species: dogs

Note: No-observed-effect level

75 000 ppm

Lowest observable effect level

100 000 ppm

Repeated dose toxicity

1,1,1,2-Tetrafluoroethane : Species: rat

NOEL: 40000 ppm

Difluoromethane : Species: rat

Application Route: Inhalation Exposure time: (90 d) NOEL: 50000 ppm Subchronic toxicity

Pentafluoroethane : Species: rat

Application Route: Inhalation Exposure time: (4 Weeks) NOEL: 50000 ppm

Subchronic toxicity

Genotoxicity in vitro

1,1,1,2-Tetrafluoroethane : Note: In vitro tests did not show mutagenic effects

Difluoromethane : Test Method: Ames test

Result: negative

Pentafluoroethane : Test Method: Ames test

Result: negative

: Cell type: Human lymphocytes

Result: negative

Method: Mutagenicity (in vitro mammalian cytogenetic test)

Test Method: Chromosome aberration test in vitro

Page 10 / 16

## Honeywell

### Genetron Performax™ LT

## 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Result: negative

: Cell type: Human lymphocytes

Result: negative

: Cell type: Chinese Hamster Ovary Cells

Result: negative

Genotoxicity in vivo

Difluoromethane : Species: mouse

Cell type: Bone marrow

Method: Mutagenicity (micronucleus test)

Result: negative

Teratogenicity

Difluoromethane : Species: rat

Dose: NOEL - 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Species: rabbit

Dose: NOEL - 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Pentafluoroethane : Species: rabbit

Application Route: Inhalation exposure

NOAEL, Teratog: 50,000 ppm NOAEL, Maternal: 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Species: rat

Application Route: Inhalation exposure NOAEL, Teratog: 50,000 ppm NOAEL, Maternal: 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Further information : Note: Vapours are heavier than air and can cause suffocation

by reducing oxygen available for breathing. Rapid

evapouration of the liquid may cause frostbite. May cause

cardiac arrhythmia.

Page 11 / 16

## Honeywell

### Genetron Performax™ LT

#### 000000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

#### **SECTION 12. ECOLOGICAL INFORMATION**

Biodegradability

Difluoromethane : Note: Minimal

Pentafluoroethane : Result: Not readily biodegradable.

Value: 5 %

Method: OECD 301 D

#### Further information on ecology

Additional ecological

information

: This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere.

To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

Note : This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

#### **SECTION 14. TRANSPORT INFORMATION**

**DOT** UN/ID No. : UN 3163

Proper shipping name : LIQUEFIED GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Difluoromethane,

Pentafluoroethane)

Class 2.2

Packing group

Hazard Labels 2.2

Page 12 / 16

## **Honeywell**

### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

IATA UN/ID No. : UN 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Difluoromethane,

Pentafluoroethane)

Class : 2.2 Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

**IMDG** UN/ID No. : UN 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(1,1,1,2-TETRAFLUOROETHANE,

DIFLUOROMETHANE, PENTAFLUOROETHANE)

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

#### **SECTION 15. REGULATORY INFORMATION**

#### **Inventories**

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic : On the inventory, or in compliance with the inventory

Page 13 / 16

## Honeywell

#### Genetron Performax™ LT

#### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

Substances and Hazardous and Nuclear Waste Control

Act

China. Inventory of Existing

Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

#### National regulatory information

**SARA 302 Components** : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

**SARA 313 Components** : SARA 313: This material does not contain any chemical

> components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

: Sudden Release of Pressure Hazard SARA 311/312 Hazards

Acute Health Hazard

California Prop. 65 : WARNING! This product contains a chemical known to the

State of California to cause cancer.

Dichloromethane 75-09-2

## **Honeywell**

#### Genetron Performax™ LT

### 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

Chloromethane 74-87-3

Massachusetts RTK : Dichloromethane 75-09-2

New Jersey RTK : Difluoromethane 75-10-5

Pennsylvania RTK : Difluoromethane 75-10-5

WHMIS Classification : A: Compressed Gas

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

#### **SECTION 16. OTHER INFORMATION**

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for

# **Honeywell**

## Genetron Performax<sup>™</sup> LT

## 00000013866

Version 1.5 Revision Date 06/04/2014 Print Date 05/28/2015

any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 09/20/2011

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group